

# 2023 CR-V

ENGINE	LX-B 2WD	LX 2WD	LX-B	LX	SPORT-B	SPORT	EX-L	TOURING HYBRID
1.5-litre, 16-valve, Direct Injection, DOHC, turbocharged 4-cylinder	•	•	•	•	•	•	•	•
2.0-litre, 16-valve, Direct Injection, DOHC 4-cylinder								•
Horsepower @ rpm <sup>1</sup>	190 @ 6000	190 @ 6000	190 @ 6000	190 @ 6000	190 @ 6000	190 @ 6000	190 @ 6000	145 @ 6100
Electric motor horsepower @ rpm <sup>1</sup>								181 @ 5000-8000
Combined total horsepower <sup>1</sup>								204
Engine torque (lb.-ft. @ rpm) <sup>1</sup>	179 @ 1700-5000	179 @ 1700-5000	179 @ 1700-5000	179 @ 1700-5000	179 @ 1700-5000	179 @ 1700-5000	179 @ 1700-5000	138 @ 4500
Combined torque @ (lb.-ft. @ rpm) <sup>1</sup>								247 @ 0-2000
Displacement (cc)	1498	1498	1498	1498	1498	1498	1498	1993
Bore and stroke (mm)	73 x 89.5	73 x 89.5	73 x 89.5	73 x 89.5	73 x 89.5	73 x 89.5	73 x 89.5	81 x 96.7
Compression ratio	10.3:1	10.3:1	10.3:1	10.3:1	10.3:1	10.3:1	10.3:1	13.9:1
Eco Assist™ system	•	•	•	•	•	•	•	•
Idle-stop	•	•	•	•	•	•	•	•
Recommended fuel	Regular	Regular	Regular	Regular	Regular	Regular	Regular	Regular
DRIVETRAIN	LX-B 2WD	LX 2WD	LX-B	LX	SPORT-B	SPORT	EX-L	TOURING HYBRID
Continuously variable transmission (CVT)	•	•	•	•	•	•	•	•
Electric-Continuously Variable Transmission (E-CVT)								•
Drive-by-Wire Throttle System™	•	•	•	•	•	•	•	•
Front-wheel drive (FWD)	•	•	•	•				
Real Time AWD™ with Intelligent Control System™			•	•	•	•	•	•
Three-mode drive system (Normal, Econ, Snow)	•	•	•	•	•	•	•	•
Four-mode drive system (Sport, Normal, Econ, Snow)								•
Steering wheel-mounted deceleration paddle selectors								•
Towing capacity <sup>2</sup> (kg)	Available 680	Available 680	Available 680	Available 680	Available 680	Available 680	Available 680	Available 453
CHASSIS	LX-B 2WD	LX 2WD	LX-B	LX	SPORT-B	SPORT	EX-L	TOURING HYBRID
17" steel wheels with silver wheel caps	•	•	•	•				
18" aluminum-alloy wheels					Black	Black	Silver	
19" aluminum-alloy wheels								Black
All-season tires	P235/65 R17 104H	P235/65 R17 104H	P235/65 R17 104H	P235/65 R17 104H	P235/60 R18 103H	P235/60 R18 103H	P235/60 R18 103H	P235/55 R19 101H
Capless fueling system	•	•	•	•	•	•	•	•
Compact spare tire	•	•	•	•	•	•	•	•
Tire repair kit								•
Electronic Parking Brake (EPB) with automatic brake hold	•	•	•	•	•	•	•	•
MacPherson strut front suspension	•	•	•	•	•	•	•	•
Motion-Adaptive Electric Power-Assisted Rack-and-Pinion Steering (EPS)	•	•	•	•	•	•	•	•
Multi-link rear suspension	•	•	•	•	•	•	•	•
Stabilizer bars – front/rear (mm)	26/17.2	26/17.2	26/12.5	26/12.5	26/12.5	26/12.5	26/12.5	26.6/13
Steering wheel turns, lock-to-lock	2.4	2.4	2.4	2.4	2.4	2.4	2.4	2.4
Power-assisted, ventilated front disc/solid rear disc brakes	•	•	•	•	•	•	•	•
ACTIVE SAFETY	LX-B 2WD	LX 2WD	LX-B	LX	SPORT-B	SPORT	EX-L	TOURING HYBRID
4-wheel Anti-lock Braking System <sup>3</sup> (ABS)	•	•	•	•	•	•	•	•
Brake Assist	•	•	•	•	•	•	•	•
Auto high beam	•	•	•	•	•	•	•	•
Collision Mitigation Braking System™ (CMBS®) <sup>3</sup> (HS*)	•	•	•	•	•	•	•	•
Forward Collision Warning (FCW) system <sup>3</sup> (HS*)	•	•	•	•	•	•	•	•
Lane Departure Warning (LDW) system <sup>3</sup> (HS*)	•	•	•	•	•	•	•	•
Electronic Brake-force Distribution (EBD)	•	•	•	•	•	•	•	•
Hill Start Assist <sup>3</sup>	•	•	•	•	•	•	•	•
Hill Descent Control	•	•	•	•	•	•	•	•
LED daytime running lights	•	•	•	•	•	•	•	•
Road Departure Mitigation (RDM) system <sup>3</sup> (HS*)	•	•	•	•	•	•	•	•
Vehicle Stability Assist <sup>3</sup> (VSA®) with Traction Control	•	•	•	•	•	•	•	•
Rear seat reminder <sup>4</sup>	•	•	•	•	•	•	•	•

HS\* = Feature is a component of the Honda Sensing® suite of safety and driver assist features.





<b>DIMENSIONS</b>	<b>LX-B 2WD</b>	<b>LX 2WD</b>	<b>LX-B</b>	<b>LX</b>	<b>SPORT-B</b>	<b>SPORT</b>	<b>EX-L</b>	<b>TOURING HYBRID</b>
Cargo volume; rear seats up/down – (L)	1113/2166	1113/2166	1113/2166	1113/2166	1113/2166	1113/2166	1113/2166	1028/2030
Curb weight – (kg)	1583	1583	1635	1635	1651	1651	1656	1785
Fuel tank capacity (L)	53	53	53	53	53	53	53	53
Gross vehicle weight rating – (kg)	2160	2160	2175	2175	2175	2175	2175	2300
Ground clearance – (mm)	198	198	208	208	208	208	208	208
Headroom – front/rear (mm)	1016/970	1016/970	1016/970	1016/970	970/970	970/970	970/970	970/970
Height (with antenna) – (mm)	1680	1680	1690	1690	1690	1690	1690	1690
Hip room – front/rear (mm)	1413/1336	1413/1336	1413/1336	1413/1336	1413/1336	1413/1336	1413/1336	1413/1336
Legroom – front/rear (mm)	1049/1042	1049/1042	1049/1042	1049/1042	1049/1042	1049/1042	1049/1042	1049/1042
Length (mm)	4695	4695	4695	4695	4695	4695	4695	4695
Passenger volume (L)	3002	3002	3002	3002	2931	2931	2931	2931
Shoulder room – front/rear (mm)	1470/1421	1470/1421	1470/1421	1470/1421	1470/1421	1470/1421	1470/1421	1470/1421
Track – front/rear – FWD (mm)	1610/1624	1610/1624	1610/1624	1610/1624	NA	NA	NA	NA
Track – front/rear – Real Time AWD™ (mm)	NA	NA	1608/1623	1608/1623	1608/1623	1608/1623	1608/1623	1608/1623
Turning radius – (m)	6.0	6.0	6.0	6.0	6.0	6.0	6.0	6.0
Wheelbase – (mm)	2701	2701	2700	2700	2700	2700	2700	2700
Width – including mirrors/mirrors folded (mm)	2150/1940	2150/1940	2150/1940	2150/1940	2150/1940	2150/1940	2150/1940	2150/1940

1. Horsepower and torque calculations reflect SAE net, Rev. 08/04, SAE J1349 procedures.

2. With the required accessory towing package. See your Owner's Manual for proper towing operation.

3. None of the features we describe are intended to replace the driver's responsibility to exercise due care while driving. Drivers should not use handheld devices or operate certain vehicle features unless it is safe and legal to do so.

Some features have technological limitations. For additional feature information, limitations and restrictions, please visit [www.honda.ca/disclaimers](http://www.honda.ca/disclaimers) and refer to the vehicle's Owner's Manual.

4. Feature uses rear door sensors only. Sensors are designed to detect if a rear door was opened and closed since the last time the vehicle was turned off. Sensors do not detect the presence of rear-seat passengers or other items.

Always check rear seats before exiting the vehicle.

5. Only compatible with certain devices and operating systems. Operation may be dependent upon: 1. GPS satellite signal reception and available cellular data and/or voice connection; or 2. connection to vehicle's built-in Wi-Fi hotspot,

if applicable. Associated charges (incl. data plans, roaming charges or other amounts charged by your wireless carrier) may apply.

6. Coverage varies by market.

7. Only available in certain areas. Includes a no-charge trial of three months.

8. Estimated fuel consumption based on Government of Canada's 5-cycle testing method. Your actual fuel consumption will vary based on driving habits and other factors – use for comparison only. For more information on 5-cycle testing,

visit <http://vehicles.nrcan.gc.ca>.

9. Map database covers major metropolitan areas in Canada and the 48 contiguous U.S. states.