

Service Information Summary

Gasoline:

Except U.S. Si
Unleaded gasoline, pump octane number of 87 or higher.
U.S. Si
Premium unleaded gasoline, pump octane number of 91 or higher.

Fuel Tank Capacity:

13.2 US gal (50 ℓ)

Recommended Engine Oil:

Except U.S. Si
API Premium grade 5W-20 detergent oil (see page 225).
Oil change capacity (including filter):
3.9 US qt (3.7 ℓ)

U.S. Si
API Premium grade 5W-30 detergent oil (see page 225).
Oil change capacity (including filter):
4.6 US qt (4.4 ℓ)

Automatic Transmission Fluid:

Honda ATF-Z1 (Automatic Transmission Fluid) preferred, or a DEXRON® III ATF as a temporary replacement (see page 232).

Manual Transmission Fluid:

Honda Manual Transmission Fluid preferred, or an SAE 10W-30 or 10W-40 motor oil as a temporary replacement (see page 233).

Capacity (including differential):

Except U.S. Si
1.5 US qt (1.4 ℓ)
U.S. Si
1.6 US qt (1.5 ℓ)

Power Steering Fluid:

Honda Power Steering Fluid preferred, or another brand of power steering fluid as a temporary replacement. Do not use ATF (see page 235).

Brake Fluid:

Honda Heavy Duty Brake Fluid DOT 3 preferred, or a DOT 3 or DOT 4 brake fluid as a temporary replacement (see page 234).

Tire Pressure (measured cold):

Front/Rear:

DX, Canadian DX-G
30 psi (210 kPa , 2.1 kgf/cm²)

LX, EX
32 psi (220 kPa , 2.2 kgf/cm²)

U.S. Si

Front:

32 psi (220 kPa , 2.2 kgf/cm²)

Rear:

29 psi (200 kPa , 2.0 kgf/cm²)

Spare Tire:

60 psi (420 kPa , 4.2 kgf/cm²)